



Rely on it.

RENOLIT ALKORPLUS₈₁₀₀₅
Protection and Separation layer



EXCELLENCE
IN ROOFING

RENOLIT ALKORPLUS₈₁₀₀₅

Protection and separation layer

Needlefelt synthetic fleece for use in RENOLIT roofing systems.

PRODUCT DATA

- synthetic fleece: 300 g/m² (short fibre); ISO 9073-1
- thickness: average 3 - 4 mm, according to ISO 9073-2
- colour: light green

APPLICATION

- as a separation layer when applying RENOLIT ALKORPLAN on a bituminous surface or on insulation such as expanded or extruded polystyrene (ballasted/mechanically fixed)
- as a protective layer
- as a compression layer
- can be used on all common surfaces
- according to the system guidelines RENOLIT ALKORPLAN - RENOLIT ALKORTOP - RENOLIT ALKORTEC

PROPERTIES

- mechanical properties
- | | | |
|------------------|---|---|
| tensile strength | M | MLV: 200 N/5 cm according to ISO 9073-3 |
| | C | MLV: 225 N/5 cm according to ISO 9073-3 |
| elongation | M | MLV: 75% according to ISO 9073-3 |
| | C | MLV: 130% according to ISO 9073-3 |
- meets all requirements for protection and separation layers
 - will not rot

PACKAGING

- | | | |
|---|----------------------|--------------------------|
| • delivery from stock | width | length |
| | 2 m | 75 m |
| • rolls are singly packed and wrapped in polyethylene film. | weight | weight per standard roll |
| | 300 g/m ² | 45 kg/roll |

WWW.RENOLIT.COM/ROOFING



Rely on it.

RENOLIT Belgium N.V - Export Dpt. - Industriepark De Bruwaan 9 - 9700 Oudenaarde - Belgium
T B +32 55 33 98 51 - F +32 55 31 86 58 - renolit.belgium@renolit.com



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Millière & côté de Rivoliobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61