



additives aglutais 30-50 improvers

Description:

AGLUTAIS 30-50 is a synthetic resin based emulsion. It is of styrene-butadiene type. When added directly to the mixture of mortars and concrete, it confers a rise in the chemical and physical resistance, as well as a faster setting. Resistant to saponification.

Uses:

AGLUTAIS 30-50 improves cohesion, mechanical resistance to compression and flexural strength, as well as adherence. It reduces plastic contraction by improving its thixotropic property. It is added to sand and cement mortars so as to improve them.

Surface preparation:

Not applicable.

Application:

- AGLUTAIS 30-50 is ready for use and is hard applied.
- It replaces mixing water.
- It must be added slowly to water until the required consistency is achieved.
- The mortar must be allowed to cure, mainly in hot weather and during the first 72 hours, by means of a curing film or by wetting it periodically.

Technical Features:

Colour/s: blanco
Density: 1.03 kg/l

Clean up:

Con abundante agua limpia.

Features & benefits:

MORE RESISTANT MORTARS. IMPROVED ADHERENCE. ENHANCED MECHANICAL RESISTANCE. IMPROVED CHEMICAL RESISTANCE.

Coverage:

In mortars 26 l for every 100 kg of cement.

Storage:

It is recommended to store this product for 3 years in its tightly closed original packages in a cool dry place, under mild temperatures and protected against bleakness.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Militaire à côté de Tovi Lobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

Normal: 1 L

5 L

25 L

60 L

Rápido: Setting accelerator: 1 L

5 L

25 L

Health and safety advice :



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Tel.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Militaire à côté de Tour Lobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61