

Description:

CECOIS is a white or grey cement-based tile adhesive, specifically designed to have enhanced properties of adhesion for fixing fully vitrified tiles and other tiles with low porosity as well as glass and porcelain mosaics without the need of an admixture. It is suitable for fixing all types of ceramic tiles and mosaics in external and internal situations. CECOIS conforms to the requirements of European UNE EN-12004.

Uses:

CECOIS adheres strongly to most construction materials such as concrete, cement and sand renders and screeds, and plasterboard.

Features & benefits:

EXCELLENT ADHERENCE. IMPROVED THIXOTROPY. EASY APPLICATION. EXCELLENT WORKABILITY. FOR INTERIORS AND EXTERIORS.

Surface preparation:

The backgrounds to receive the ceramic tiles should be mature and stable. Backgrounds to receive ceramic tiles should be finished to Surface Regularity.

Application:

- CECOIS is mixed directly with water in the required proportion until reaching the desired consistency.
- Mix manually or using a low speed mixer (400 - 500 rpm)
- The proportion of the mix is 280 to 320 cm³ of water per kg of CECOIS.
- CECOIS is spread onto the support using a serrated trowel, by spreading the amount proportional to the open time of the mix which is 30 minutes approximately according to temperature. (lower open time at higher temperature).
- Place the pieces by twisting them into place so as to spread the adhesive onto the whole surface.
- In hot weather or for poorly absorbent surfaces, it is recommended to slightly dampen the support.
- Expansion joints can arise for those pieces found in exteriors according to the expansion of the pieces.

Technical Features:

Powder density: 1.275 ± 0.05 g/cc
Mass of density: 1.850 ± 0.05 g/cc
Curing density: 1.650 ± 0.05 g/cc
Water absorption: 25 ± 3%
Adherence: > 0.5 N/mm²
Colour/s: Gris and blanco

Coverage:

2.5 kg per m² in 2mm thick coating.

Clean up:

Tools must be cleaned with water before the material hardens.

Storage:

It is recommended to store this product for 2 years in its tightly closed original packages, protected against bleakness, in a cool dry place.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Mars Militaire 3 coin de Touilobe
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

Blanco: 1 Kg

5 Kg

25 Kg

Gris: 1 Kg

5 Kg

25 Kg

Health and safety advice :

R36/37/38 -- Irritating to eyes, respiratory system and skin


S2 -- Keep out of the reach of children

S8 -- Keep container dry

S24/25 -- Avoid any inhalation, contact with skin and eyes. Wear suitable protective clothing and gloves

S26 -- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S37/39 -- Wear suitable gloves and eye/face protection



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Tel.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
 Jonquet Face MTN Internet
 TÉL.: (+229) 21 33 33 48
 95 96 00 08

04 B P : 0526 Cotonou
 contact@hpbenin.com
 www.hpbenin.com

DIRECTION COMMERCIALE
 HBP New City
 Maro Militaire à côté de Taxi Lobo
 Tél.: (+229) 21 32 48 48
 95 02 72 72 - 94 00 61 61