

Description:

CECOISFLEX is a high performance (C2), flexible cementitious adhesive (S1) with extended open time (E) and no vertical slip (T) for all kinds of ceramic tiles; it conforms to the requirements of UNE EN-12004 european standard. For interior and exterior use.

Uses:

This cement based adhesive is suitable for fixing a variety of floor and wall tiles such as low-porosity tile, slate, marble, granite, porcelain, vitrified, semi vitrified to different surfaces as plasterboard and underfloor heating system.

Surface preparation:

Before commencing, all surfaces must be clean, dry and strong enough to support the weight of the tiles and the adhesive. Remove all loose dust, dirt oil, grease and other contaminants likely to affect adhesion. New brickwork, blockwork and concrete, must be fully cured and dry prior to tiling.

Application:

- CECOISFLEX powder should be added slowly (by hand or using a slow mechanical mixing paddle) to clean water in a suitable container in the appropriate proportion of 25 kg powder to 6 liters water.
- Mix until a smooth consistency is achieved, leave to stand for 2 minutes then remix.
- Do NOT use in temperatures below 5°C or in damp conditions
- Press tile firmly into the ribs of the adhesive and into position, with slight twisting/sliding action to ensure optimum adhesive contact.

Technical Features:

Water absorption: $25 \pm 3 \%$
Adherence: $> 1.0 \text{ N/mm}^2$
Curing density: $1.650 \pm 0.05 \text{ g/cc}$
Mass of density: $1.850 \pm 0.05 \text{ g/cc}$
Application temperature: C2 T E S1

Clean up:

Tools must be cleaned with water.

Features & benefits:

EXCELLENT ADHERENCE. IMPROVED MECHANICAL RESISTANCE.
ENHANCED WORKABILITY. SUITABLE FOR INTERIOR AND EXTERIOR

Coverage:

3 kg per m² in 2mm thick coating.

Storage:

Protect from frost, damp and bleakness. It's shelf life under normal dry conditions is 12 months.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P - 0526 Cotonou
contact@hbphenin.com
www.hbphenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Milinaire 3 coté de Touilobo
Tél.: (+229) 21 32 49 48
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

White: 25 Kg

Grey: 25 Kg

Health and safety advice :

R36/37/38 -- Irritating to eyes, respiratory system and skin

S2 -- Keep out of the reach of children

S8 -- Keep container dry

S24/25 -- Avoid any inhalation, contact with skin and eyes. Wear suitable protective clothing and gloves

S26 -- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S37/39 -- Wear suitable gloves and eye/face protection



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Tel.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
 Jonquet Face MTN Internet
 Tél.: (+229) 21 33 33 48
 95 96 00 08

04 B P : 0526 Cotonou
 contact@hbpenin.com
 www.hbpenin.com

DIRECTION COMMERCIALE
 HBP New City
 Mare Militaire à côté de Yexi Lobo
 Tél.: (+229) 21 32 48 48
 95 02 72 72 - 94 00 61 61