

Description:

PLAIS N a plasticiser for mortars and concrete. It improves flexibility, manoeuvrability and laying out of mortars and concrete.

Uses:

PLAIS N is used for improving manoeuvrability of mortars and concrete. It thus enables to reduce the A/C ratio so as to obtain an improved finish for moulded pieces by increasing their mechanical resistance.

Features & benefits:

IT IMPROVES MANOEUVRABILITY CONSIDERABLY. IT ALLOWS FOR WATER REDUCTION. IT IMPROVES CEMENT HYDRATION. BONDING CAPACITY IS IMPROVED. WATERPROOFING IS ENSURED.

Surface preparation:

Not applicable.

Application:

- PLAIS N is added to water upon mixing in the proportion of 1 litre for every 10.000 kg of cement (200 bags).
- Por cada saco de cemento de 50 kg, se agregan 20 cc de Plais N al agua de amasado.
- It is recommended to add 20 cm³ of PLAIS N to mixing water for every 50 kg of cement.

Technical Features:

Colour/s: marrón oscuro.
Density: 1.03 Kg/L (±) 0.05 g/cm³.
PH: 7 ± 1

Coverage:

Clean up:

Tools must be cleaned with large amounts of water.

Storage:

It is recommended to store this product for 3 years in its tightly closed original packages in a cool dry place at temperatures above 4°C.

Packaging:

Available in packs of:

Normal: 200 L

- 1 L
- 5 L
- 25 L



Health and safety advice :

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.