

### Description:

VELOAIS ESPECIAL consists of a group of rocky fibres joined together with resin so as to prevent the formation of micro-fissures.

### Uses:

It is used in interiors and exteriors (for new restoration works). Applicable in humid or dry environments, by using the appropriate paints that are required according to the desired use or support of application.

### Surface preparation:

Not applicable.

### Application:

- Apply on the appropriate undercoating of paint.
- Whilst the paint is still fresh, add VELOAIS using a foam roller, without forming air bags or markings.
- Repeat successively by overlapping VELOAIS in 2 to 3 cm layer thickness (when waterproofing) or simply overlap completely (when decorating).
- Once the paint-VELOAIS combination is dry, finish by applying smooth or corrugated paint.

### TechnicalFeatures:

Density: 30 g/m<sup>2</sup>

- : It is dimensionally stable and inert in alkaline environments.
- : It is not altered by variations in temperature and humidity.

Elongation until breaking point: 35%

Resistance to longitudinal tear: >2 daN

Resistance to traction: 3.5 daN.

Average thickness: 0.31 mm.

Softening point: +140 to +150°C

- : It reinforces paints without causing any micro-fissures.
- : It does not undergo rotting (100% polypropylene)

### Clean up:

Not applicable.

### Features & benefits:

FOR REINFORCING PAINTS.FOR IMPROVED WATERPROOFING.

### Coverage:

1 m<sup>2</sup> per m<sup>2</sup>.

### Storage:

It is recommended to store this product in its original rolls, in a dry place and protected from bleakness. No limit time for storage.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Tel.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE  
Jonquet Face MTN Internet  
Tél.: (+229) 21 33 33 48  
95 96 00 08

04 B P : 0526 Cotonou  
contact@hpbbenin.com  
www.hpbbenin.com

DIRECTION COMMERCIALE  
HBP New City  
Maro Militaire à côté de Taxi Lobo  
Tél.: (+229) 21 32 48 48  
95 02 72 72 - 94 00 61 61



# insulation veloais especial

felts

## Packaging:

Available in packs of:

Rolls of 50 x 0.50 m: 25 m<sup>2</sup>

## Health and safety advice :



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



### PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña  
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE  
Jonquet Face MTN Internet  
Tél.: (+229) 21 33 33 48  
95 96 00 08

04 B P : 0526 Cotonou  
contact@hbpenin.com  
www.hbpenin.com

DIRECTION COMMERCIALE  
HBP New City  
Maro Militaire à côté de Toki Lobo  
Tél.: (+229) 21 32 48 48  
95 02 72 72 - 94 00 61 61