

Description:

REPOIS R consists of a cement based external through coloured render. It is formed by a mortar that is freshly applied and allowed to dry partially. A special trowel is then used so as to obtain a decorative scratched finish.

Uses:

It is used for rendering facades made of blockwork or brickwork. It also gives uniformity to new jobs performed on concrete, brickwork, etc. It is also used for restoring purposes so as to replace paints and plastic renders.

Features & benefits:

WATERPROOFING.MAXIMUM RESISTANCE.EXCELLENT DURABILITY.ENHANCED DECORATIVE PROPERTIES.

Surface preparation:

The background of application must be clean, resistant, free of grease, oil, uniform, free of any ridges or irregularities, by being slightly damp.

Application:

- Mix with water in a proportion of 19 ? 3% of water in weight, manually or mechanically(concrete mix, slow mixer, etc).
- Apply the fresh mortar mix onto the support to be rendered using a trowel and then smoothen with a ruler. Proceed to limit the piers by placing the joints in the desired pattern: 7 m vertically and 2.5 m horizontally). Leave to dry partially. After 24 hours(depending on weather conditions), use a special trowel so as to achieve a scraped finish.
- It is recommended to apply at least 10 mm thick coating and reaching an average thickness of 15 mm.

TechnicalFeatures:

Water absorption: $19 \pm 3\%$
Powder density: 1.350 ± 0.05 g/cc.
Mass of density: 1.750 ± 0.05 g/cc.
Curing density: 1.800 ± 0.05 g/cc.
Capillarity: Water retention: $> 97\%$
Adherence: > 2.5 kg/cm²
Compressive resistance: > 80 kg/cm²
Flexural strength resistance: > 35 kg/cm²
Colour/s: gris, blanco, crema, castilla, ocre, rosa, etc. (various colours according to colour chart).

Coverage:

20kg and 22kg per m² for white colour.

Clean up:

Clean using large amounts of water.

Storage:

It is recommended to store this product for 1 year in tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpenin.com
www.hbpenin.com

DIRECTION COMMERCIALE
HBP New City
Moro Millaire à côté de Toki Lobo
Tél.: (+229) 21 32 48 49
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

Ocre, Amarillo, Gris, Rosa, Salmón: 25 Kg

Blanco, Marfil, Crema, Arena: 25 Kg

Terracota, Tostado, Teja, Marrón, Verde: 25 Kg

Health and safety advice :

R36/37/38 -- Irritating to eyes, respiratory system and skin

S2 -- Keep out of the reach of children

S8 -- Keep container dry

S24/25 -- Avoid any inhalation, contact with skin and eyes. Wear suitable protective clothing and gloves

S26 -- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S37/39 -- Wear suitable gloves and eye/face protection



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Tel.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
 Jonquet Face MTN Internet
 Tél.: (+229) 21 33 33 48
 95 96 00 08

04 B.P. - 0526, Cotonou
 contact@hbpbenin.com
 www.hbpbenin.com

DIRECTION COMMERCIALE
 HBP New City
 Marc Milière - Coste de Toul - Lobo
 Tél.: (+229) 21 32 48 48
 95 02 72 72 - 94 00 61 61