

# waterproofing

contention walls waterproof

# **Description:**

LASTOIS IN is a paint composed chemically, based on petrochemical resins, tar coal and asphalt oil which form a waterproofing barrier.

#### Uses:

It is ideal for waterproofing terraces, contention walls, cracks, dams, party walls, etc. Used for priming in supports that are protected with Aluminium or asphalt sheets so as to improve adherence. For protecting and covering metallic reinforced structures so as to prevent corrosion and to avoid contact of wood with earth, etc.

#### Features & benefits:

STABLE TO PERMANENT WATER CONTACT.EXCELLENT DURABILITY.FLEXIBILITY.

#### Surface preparation:

The background should clean and completely dry, free of grease, oil, loose particles, fungus and mould.

# **Application:**

- Apply using a paint brush or roller.

- WATERPROOFING: Apply two coating in a crosswise manner, Dos manos cruzadas, leaving 10 hours in between each coating.
- PRIMING: Apply one single coating and leave to dry 10 hours (after this time interval, the sheets are placed followed by pouring the aggregates, water, etc).

## **TechnicalFeatures:**

Density: 0.97 Kg/L ± 0.01 Aspect: Matt. -: Resistant to diluted acids, alkalis and atmospheric corrosion. -: Great penetrating and covering power.

# Clean up:

Tools must be cleaned using our greasy solvent DISOLUAIS.

#### **Coverage:**

2 m2 per l.

#### Storage:

It is recommended to store this product for 1 year in its tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS ©TEAIS S.A. - All rigths reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



nou HBP New com Maro Militaire à c om Tél.: (+229) 2 95 02 72 72



# waterproofing lastois in

contention walls waterproof

### Packaging:

Available in packs of: .: 0.75 L 4 L 20 L 200 L

# Health and safety advice :

R10 -- Flammable

- R37 -- Irritating to respiratory system
- R66 -- Repeated exposure may cause skin dryness or cracking
- R67 -- Vapours may cause drowsiness and dizziness

R51/53 -- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment :

S61 -- Avoid release to the environment. Refer to special instructions/safety data sheet





The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS ©TEAIS S.A. - All rigths reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es

