

Description:

REPAIS is a resin based on low molecular siloxano-oligomer structure. It facilitates penetration in the interior of the support without leaving waste or shine. It achieves a watertight effect without preventing the material to breathe. It also allows dilution of soluble salts, acting as a complete waterproofing product.

Uses:

It is used for waterproofing facades made of brick and concrete slips, marble, granite, mineral renders, ceramic roof tiles, etc.

Features & benefits:

WATERPROOFING.NO STEAM BARRIER.EXCELLENT DURABILITY.UNALTERED DECORATIVE ASPECT.

Surface preparation:

The background of application must be clean and dry, ensuring proper setting(at least 20 days).

Application:

- It is hard applied (without diluting) by using a paint brush, roller or spray in a continuous manner and avoiding any overlapping.
- Apply as many coatings as necessary (depending on the absorption of the support).
- Avoid direct sun exposure. It is recommended to work under temperatures ranging from 10 to 25°C.

TechnicalFeatures:

Density: 0.79 Kg/L \pm 0.05 at 20°C.

- : It reduces moisture content to 90% in the material.
 - : It reduces the capacity of contamination of the support.
 - : It prevents the formation of efflorescence of soluble salts and protects against rain and frost.
 - : It reduces the risk of the support of breaking due to frost.
 - : It maintains wall breathing unaltered.
- Combustion point: above +70°C.
- : It has a great damp-proof effect(penetrating up to 5 mm).
 - : It is stable to UV rays.

Coverage:

6 m2 per l.

Clean up:

Clean using our solvent DISOLUAIS B.

Storage:

It is recommended to store this product for 3 years in tightly closed original packages in a cool dry place.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jouquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B.P. : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Moro Millière à côté de l'axe Loko
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

:: 0.75 L
5 L
20 L
60 L

Health and safety advice :

R11 -- Highly flammable
R20 -- Harmful by inhalation
R51/53 -- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment :
R65 -- Harmful : may cause lung damage if swallowed
R66 -- Repeated exposure may cause skin dryness or cracking
R67 -- Vapours may cause drowsiness and dizziness
S2 -- Keep out of the reach of children
S16 -- Keep away from sources of ignition - No smoking
S25 -- Avoid contact with eyes
S29 -- Do not empty into drains
S33 -- Take precautionary measures against static discharges
S46 -- If swallowed, seek medical advice immediately and show this container or label



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotenuu
contact@hbphenin.com
www.hbphenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Militaire 3091 de Tadj Labo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61