



S

WOODSTAIN

Matt / Satin / Smooth

1. DESCRIPTION

Product Type

Solvent-borne woodstain for providing protection against UV rays, rain, humidity and delays formation of moulds on the surface.

Advantages

- Xylazel S Woodstain protects wood from the suns harmful UV rays, rain and humidity.
- It has been specially developed to give long lasting protection and excellent resistance.
- Matt, satin and smooth finish.
- Translucent and intermixable colours.
- It enhances natural wood grain.
- It penetrates deep into wood without building a barrier.
- Permeable resins. It allows wood to breathe.
- Easy to apply and maintain.
- Low odour formula. Once dried, it does not smell.

Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, furniture and any wood piece.

Colours

Matt: pine, light pine, iroko, red pine, teak, jatoba, green fir, chestnut, walnut, rosewood, ebony, colourless.
 Satin: light oak, red pine, light pine, pine, sapelly, chestnut, oak, green fir, walnut, mahogany, teak, colourless.
 Smooth: pine, oak, teak, mahogany, oak and colourless.

Packaging

Matt and Satin:

375 ml, 750 ml, 2,5 litres and 5 litres.

Smooth: 750 ml and 5 litres.

2. TECHNICAL DATA

Density at 20°C:

Matt: 0.85±0.015g/mL.

Satin: 0.92±0.01g/mL.

Smooth: 0.91±0.01 g/L.

Touch dry: 6 hours.

Second coat: 12 hours.

Matt: 2004/42/IIA (f) (700/700) Max COVs 690 g/L.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

It is deemed necessary to apply Xylazel Wood Preserver to provide protection against decay and insects.

In "oily" timbers such as teak and iroko, it is recommended to apply Xylazel Exotic Woods Primer.

Covering capacity

Matt: 150 to 200 mL/m².

Satin and Smooth: > 140 mL/m².

Application

Stir the product thoroughly.

Xylazel S Woodstain is ready to use, you should not dilute it with solvent or any other product. For the possible finish use a good quality brush or a spray gun. Apply one or two coats. Lightly sand and clean dust between coats.

Maintenance

Easy maintenance, there is no need to sand, simple apply more Xylazel S Woodstain when needed.

The period between maintenance application will vary and is dependent upon the degree of exposure, elevation, design of the component, quality of timber and original application.

The need for maintenance is indicated by lightening in colour and reduction in sheen as the coating erodes, and loss of water appearance.

Cleaning equipment

Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Do not apply if the room temperature is below 5°C or over 30°C during application and drying or in conditions of high humidity.

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



DIRECTION GÉNÉRALE
 Jonquet Face MTN Internet
 Tél.: (+229) 21 33 33 48
 95 96 00 08

04 B P : 0526 Cotonou
 contact@hbpbenin.com
 www.hbpbenin.com

DIRECTION COMMERCIALE
 HBP New City
 Mareuilville code de Postale
 Tél.: (+229) 21 32 48 48
 95 02 72 72 - 94 00 61 61

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com

